

M27 SLD G

SPECIFICATIONS

Nominal Voltage (V)	12V
Capacity at C/100	99 Ah
Capacity at C/20	88 Ah
Weight	63 lbs. (28.6 kg)
Plate Alloy	Lead Calcium
Posts	Forged Terminals & Bushings
Container/Cover	Polypropylene
Operating Temperature Range	-76°F (-60°C) - 140°F (60°C)
Charge Voltage @ 68°F (20°C)	
Cycle	2.30 - 2.35 VPC
Float	2.25 - 2.30 VPC
Vent	Self-sealing
Electrolyte	Sulfuric acid thixotropic gel
Terminal	B (T876)



Rated non-spillable by ICAO, IATA and DOT

Made in the U.S.A. by East Penn Manufacturing Co, Inc.


Valve-Regulated, Gelled-Electrolyte Battery



DIMENSIONS

Length (mm)	12.83 (326 mm)
Width (mm)	6.56 (167 mm)
Height (mm)	9.30 (236 mm)

Gel Cycle Life vs Depth of Discharge at +25°C (77°F)
Based on BCI 2-hour Capacity



MK Battery

1631 South Sinclair Street • Anaheim, California 92806

Toll Free: 800-372-9253 • Fax: 714-937-0818 • E-mail: sales@mkbattery.com

