PRODUCT SPECIFICATIONS SHEET
Model: Jazzy Passport
Document Information: INFINFB3838/Rev B/December 2017

Class of Use	A
Weight Capacity	250 lbs. (113 kg/17 stone 12 lbs.)
Maximum Speed[1]	Up to 3.6 mph (5.8 km/h)
Ground Clearance[2]	3 in. (79 mm) at motor
Turning Radius[2]	24.25 in. (616 mm)
Overall Size[2, 6]	Length: 40 in. (1016 mm) Width: 23.5 in. (597 mm)
Drive Wheels	12 in. (305 mm), pneumatic
Caster Wheels	8 in. (203 mm), solid
Anti-tip Wheels	1.75 in. (44 mm)
Suspension	Limited
Range[1, 4]	Up to 9.6 miles (15 km)
Component Weights[5]	Complete Assembly (without battery): 54 lbs. (24 kg) Battery: 7 lbs. (3.3 kg)
Drivetrain	Two motor, rear-wheel drive
Brakes	"Intelligent Braking" electronic regenerative, disc park brake
Battery[3]	One 25.2V 18.2 Ah Lithium-Ion battery
Battery Charger	2 amp, off-board
Freewheel Operational Force	Less than 60 N
Drive Control Operational Force	Less than 5 N
Maximum Rated Slope	6° (10.5%)
Maximum Obstacle Climbing Ability (Ascending and Descending)	1.5 in. (40 mm)
Measured Sound Level (A-weighted)	Less than 65 dB

[1] Varies with base model, user weight, terrain type, battery amp hour rating (Ah), battery charge, battery condition, motors, controller type, tire type, and tire condition. This specification is subject to a variance of +10%, -5%.

[2] Due to manufacturing tolerances and continued product improvement, this specification can be subject to a variance of (+ or -) 3%.

[3] Lithium-Ion type required. See "Batteries and Charging."

[4] Tested in accordance with ANSI/RESNA, WC Vol. 2, Section 4 & ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive system performance. Test conducted at maximum weight capacity.

[5] Battery weight may vary based on manufacturer.

[6] Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.

NOTE: This product conforms to all applicable ANSI/RESNA, ISO 7176 Series, AS/NZS 3695.2, and EN12184 standards. All specifications subject to change without notice.

LENGTH
40 in. (1016 mm)

WIDTH
23.5 in. (597 mm)

TURNING RADIUS

24.25 in.
(616 mm)

3 in. (79 mm)
AT MOTOR
GROUND CLEARANCE